SAFETY DATA SHEET

This Safety Data Sheet conforms to ANSI Z400.5, and to the format requirements of the Global Harmonizing System.

THIS SDS COMPLIES WITH 29 CFR 1910.1200 (HAZARD COMMUNICATION STANDARD) IMPORTANT: Read this SDS before handling & disposing of this product. Pass this information on to employees, customers, & users of this product.

SECTION 1. IDENTIFICATION OF THE SUBSTANCE OR MIXTURE AND OF THE SUPPLIER

PRODUCT IDENTITY: FILTER FREE CS27
PRODUCT PURPOSE: SPOTTER
COMPANY IDENTITY: Bridgepoint Systems

COMPANY ADDRESS: 4282 S 590 W COMPANY CITY: Salt Lake City, UT 84123

1-800-658-5314 COMPANY PHONE:

EMERGENCY PHONES: INFOTRAC: 1-800-535-5053 (USA)

SECTION 2. HAZARDS IDENTIFICATION

DANGER!!

DANGER;;				
HAZARD STATEMEN	NTS:			
H100s = Gener	ral, H200s = Physical, H300s = Health, H400s = Environmental			
H226	COMBUSTIBLE LIQUID(N.America);			
	FLAMMABLE LIQUÍD & VAPOR(Elséwhere)			
H302	HARMFUL IF SWALLOWED.			
H304	MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS.			
H315	CAUSES SKIN IRRITATION			
H317	MAY CAUSE AN ALLERGIC SKIN REACTION.			
H320	CAUSES EYE IRRITATION.			
H335	MAY CAUSE RESPIRATORY IRRITATION			
H336	MAY CAUSE DROWSINESS OR DIZZINESS			
PRECAUTIONARY STATEMENTS: EXPOSURE PREVENTION: STRICT HYGIENE!				
P100s = General, P200s = Prevention, P300s = Response, P400s = Storage, P500s = Disposal				
P264	Wash with soap & water thoroughly after handling.			
P270	Do not eat, drink or smoke when using this product.			
P271	Use only outdoors or in a well-ventilated area.			
P280	Wear protective gloves/protective clothing/eye protection/face protection.			
P301+312	IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.			
P302+352	IF ON SKIN: Wash with soap & water.			
P304+340	IF INHALED: Remove victime to fresh air & keep at rest in a position			
	comfortable for breathing.			
P305+351+338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact			
	lenses if present & easy to do - Continue rinsing.			
P330	Rinse mouth.			

SEE SECTIONS 8, 11 & 12 FOR TOXICOLOGICAL INFORMATION.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

MATERIAL	CAS#	EINECS#	WT %
Potassium Pyrophosphate	7320-34-5	-	Trade Secret
d-Limonene .	5989-27-5	227-813-5	Trade Secret

TRACE COMPONENTS: Trace ingredients (if any) are present in < 1% concentration, (< 0.1% for potential carcinogens, reproductive toxins, respiratory tract mutagens, and sensitizers). None of the trace ingredients contribute significant additional hazards at the concentrations that may be present in this product. All pertinent hazard information has been provided in this document, per the requirements of the Federal Occupational Safety and Health Administration Standard (29 CFR 1910.1200), U.S. State or and Canadian Hazardous Matanials Identification System Standard (CFR 4) equivalents, and Canadian Hazardous Materials Identification System Standard (CPR 4).

If skin irritation occurs: Get medical advice/attention. If eye irritation persists, get medical advice/attention.

SECTION 4. FIRST AID MEASURES

MOST IMPORTANT SYMPTOMS/EFFECTS, ACUTE & CHRONIC: See Section 11 for Symptoms/Effects (acute & chronic).

EYE CONTACT:

P332+313 P337+313

For eyes, flush with plenty of water for 15 minutes & get medical attention.

COMPANY IDENTITY: Bridgepoint Systems SDS DATE: 04/20/2014 PRODUCT IDENTITY: FILTER FREE ORIGINAL: 04/20/2014

SECTION 4. FIRST AID MEASURES (CONTINUED)

In case of contact with skin immediately remove contaminated clothing. Wash thoroughly with soap & water. Wash contaminated clothing before reuse.

INHALATION:

After high vapor exposure, remove to fresh air. If breathing is difficult, give oxygen. If breathing has stopped, trained personnel should immediately begin artificial respiration. If the heart has stopped, trained personnel should immediately begin cardiopulmonary resuscitation (CPR).

SWALLOWING:

Rinse mouth. Do NOT induce vomiting. GET MEDICAL ATTENTION IMMEDIATELY. Do NOT give liquids to an unconscious or convulsing person.

SECTION 5. FIRE FIGHTING MEASURES

FIRE & EXPLOSION PREVENTIVE MEASURES:

NO open flames, NO sparks, & NO smoking. Above flash point, use a closed system, ventilation, explosion-proof electrical equipment, lighting.

SUITABLE (& UNSUITABLE) EXTINGUISHING MEDIA:

Use dry powder, AFFF, alcohol-resistant foam, water spray, carbon dioxide.

SPECIAL PROTECTIVE EQUIPMENT & PRECAUTIONS FOR FIRE FIGHTERS: Water spray may be ineffective on fire but can protect fire-fighters & cool closed containers. Use fog nozzles if water is used. Do not enter confined fire-space without full bunker gear. (Helmet with face shield, bunker coats, gloves & rubber boots).

SPECIFIC HAZARDS OF CHEMICAL & HAZARDOUS COMBUSTION PRODUCTS:

COMBUSTIBLE! Isolate from oxidizers, heat, & open flame. Closed containers may explode if exposed to extreme heat. Applying to hot surfaces requires special precautions. Empty container very hazardous! Continue all label precautions!

SECTION 6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT & EMERGENCY PROCEDURES: Keep unprotected personnel away. Remove all ignition sources. Filter respirator for organic vapors.

ENVIRONMENTAL PRECAUTIONS:

Keep from entering storm sewers and ditches which lead to waterways.

METHODS & MATERIAL FOR CONTAINMENT & CLEAN-UP:

Stop spill at source. Dike and contain. Absorb remaining liquid in sand or inert absorbent. Remove to safe place.

SECTION 7. HANDLING AND STORAGE

PRECAUTIONS FOR SAFE HANDLING:

Isolate from oxidizers, heat, & open flame. Use only with adequate ventilation. Avoid breathing of vapor or spray mist. Avoid prolonged or repeated contact with skin. Wear OSHA Standard goggles or face shield. Consult Safety Equipment Supplier. Wear goggles, face shield, gloves, apron & footwear impervious to material. Wash clothing before reuse. Avoid free fall of liquid. Ground containers when transferring. Do not flame cut, braze, or weld. Empty container very hazardous! Continue all label precautions!

CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES:
Keep in fireproof surroundings. Keep separated from strong oxidants.
Store in an area without a drain or sewer access. Do not store above 49 C/120 F.
Keep container tightly closed & upright when not in use to prevent leakage.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

EXPOSURE LIMITS:

CAS# TWA (OSHA) TLV (ACGIH) MATERIAL EINECS# POTASSIUM PYROPHOSPHATE 7320-34-5 None Known None Known 5989-27-5 227-813-5 None Known d-Limonene None Known

```
This product contains no EPA Hazardous Air Pollutants (HAP) in amounts > 0.1%.
COMPANY IDENTITY: Bridgepoint Systems SDS DATE: 04/20/2014
```

PRODUCT IDENTITY: FILTER FREE ORIGINAL: 04/20/2014

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION (CONTINUED)

APPROPRIATE ENGINEERING CONTROLS:

RESPIRATORY EXPOSURE CONTROLS

A respiratory protection program that meets OSHA 29 CFR 1910.134 and ANSI Z86.2 requirements or European Standard EN 149 must be followed whenever workplace conditions warrant a respirator's use.

VENTILATION

LOCAL EXHAUST: Necessary MECHANICAL (GENERAL): Acceptable SPECIAL: None OTHER: None Please refer to ACGIH document, "Industrial Ventilation, A Manual of Recommended Practices", most recent edition, for details.

INDIVIDUAL PROTECTION MEASURES, SUCH AS PERSONAL PROTECTIVE EQUIPMENT:

PERSONAL PROTECTIONS:

Wear OSHA Standard goggles and gloves as a standard practice.

SECTION 9. PHYSICAL & CHEMICAL PROPERTIES

```
APPEARANCE:
                                                                                              Cloudy Liquid
ODOR:
                                                                                              OrangeLemon
ODOR THRESHOLD:
                                                                                              Not Ăvailable
                                                                                               10.4
 pH (Neutrality)
MELTING POINT/FREEZING POINT:
BOILING RANGE (IBP,50%,Dry Point):
FLASH POINT (TEST METHOD):
EVAPORATION RATE (n-Butyl Acetate=1):
FLAMMABILITY CLASSIFICATION:
                                                                                              Not Available
                                                                                              > 100 C / > 212 F
> 51 C / > 125 F (TCC)
Not Applicable
                                                                                              Class II
LOWER FLAMMABLE LIMIT IN AIR (% by vol):
UPPER FLAMMABLE LIMIT IN AIR (% by vol):
VAPOR PRESSURE (mm of Hg)@20 C
VAPOR DENSITY (air=1):
GRAVITY @ 68/68 F / 20/20 C:
DENSITY:
                                                                                              1.0 (Lowest Component)
Not Available
                                                                                              17.5
                                                                                              0.688
                                                                                              1.047
      SPECIFIC GRAVITY (Water=1):
                                                                                              1.048
      POUNDS/GALLON:
                                                                                              8.730
WATER SOLUBILITY:
                                                                                              Appreciable
PARTITION COEFFICIENT (n-Octane/Water):
                                                                                              Not Available
AUTO IGNITION TEMPERATURE: DECOMPOSITION TEMPERATURE:
                                                                                              260 C / 500 Not Available
                                                                                                               500 F
VOCs (>0.044 Lbs/Sq In):
TOTAL VOC'S (TVOC)*:
NONEXEMPT VOC'S (CVOC)*:
HAZARDOUS AIR POLLUTANTS (HAPS):
                                                                                              Not Available
                                                                                              0.22 Lbs/Gal
                                                                                              0.00 Lbs/Gal
                                                                                              0.0
                                                                                                      Wt%
NONEXEMPT VOC PARTIAL PRESSURE (mm of Hg @ 20 C) No VISCOSITY @ 20 C (ASTM D445): No * Using CARB (California Air Resources Board Rules).
                                                                                              Not Available
                                                                                              Not Available
```

SECTION 10. STABILITY & REACTIVITY

REACTIVITY & CHEMICAL STABILITY: Stable under normal conditions.

POSSIBILITY OF HAZARDOUS REACTIONS & CONDITIONS TO AVOID: Isolate from oxidizers, heat, & open flame.

INCOMPATIBLE MATERIALS:

Reacts with strong oxidants, causing fire & explosion hazard.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon Monoxide, Carbon Dioxide, Potassium Oxide & Hydroxide from burning.

HAZARDOUS POLYMERIZATION: Will not occur.

COMPANY IDENTITY: Bridgepoint Systems

SDS DATE: 04/20/2014 PRODUCT IDENTITY: FILTER FREE ORIGINAL: 04/20/2014

SECTION 11. TOXICOLOGICAL INFORMATION

ACUTE HAZARDS

EYE & SKIN CONTACT:

Primary irritation to skin, defatting, dermatitis. Primary irritation to eyes, redness, tearing, blurred vision. Liquid can cause eye irritation. Wash thoroughly after handling.

INHALATION:

Anesthetic. Irritates respiratory tract. Acute overexposure can cause serious nervous system depression. Vapor harmful.

SWALLOWING:

Harmful or fatal if swallowed.

Swallowing can cause abdominal irritation, nausea, vomiting & diarrhea. The symptoms of chemical pneumonitis may not show up for a few days.

SUBCHRONIC HAZARDS/CONDITIONS AGGRAVATED

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:

Pre-existing disorders of any target organs mentioned in this SDS can be aggravated by over-exposure by routes of entry to components of this product. Persons with these disorders should avoid use of this product.

CHRONIC HAZARDS

CANCER, REPRODUCTIVE & OTHER CHRONIC HAZARDS This product has no carcinogens listed by IARC, NTP, NIOSH, OSHA or ACGIH, as of this date, greater or equal to 0.1%.

TARGET ORGANS: May cause damage to target organs, based on animal data.

IRRITANCY: Irritating to contaminated tissue.

SENSITIZATION: No component is known as a sensitizer.

MUTAGENICITY: No known reports of mutagenic effects in humans.

EMBRYOTOXICITY: No known reports of embryotoxic effects in humans.

TERATOGENICITY: No known reports of teratogenic effects in humans.

REPRODUCTIVE TOXICITY: No known reports of reproductive effects in humans.

A MUTAGEN is a chemical which causes permanent changes to genetic material (DNA) such that the changes will propagate across generational lines. An EMBRYOTOXIN is a chemical which causes damage to a developing embryo (such as: within the first 8 weeks of pregnancy in humans), but the damage does not propagate across generational lines. A TERATOGEN is a chemical which causes damage to a developing fetus, but the damage does not propagate across generational lines. A REPRODUCTIVE TOXIN is any substance which interferes in any way with the reproductive process.

MAMMALIAN TOXICITY INFORMATION

No mammalian information is available on this product.

SECTION 12. ECOLOGICAL INFORMATION

ALL WORK PRACTICES MUST BE AIMED AT ELIMINATING ENVIRONMENTAL CONTAMINATION.

EFFECT OF MATERIAL ON PLANTS AND ANIMALS:

This product may be harmful to plant and animal life if released into the environment. Refer to Section 11 (Toxicological Information) for further data on the effects of this product's components on test animals.

EFFECT OF MATERIAL ON AQUATIC LIFE:

No aquatic environmental information is available on this product.

MOBILITY IN SOIL

This material is a mobile liquid.

DEGRADABILITY

This product is completely biodegradable.

ACCUMULATION

Bioaccumulation of this product has not been determined.

COMPANY IDENTITY: Bridgepoint Systems

PRODUCT IDENTITY: FILTER FREE

SDS DATE: 04/20/2014 ORIGINAL: 04/20/2014

SECTION 13. DISPOSAL CONSIDERATIONS

Processing, use or contamination may change the waste disposal requirements. Do not dispose of on land, in surface waters, or in storm drains. Waste should be recycled or disposed of in accordance with regulations. Large amounts should be collected for reuse or consigned to licensed hazardous waste haulers for disposal.
ALL DISPOSAL MUST BE IN ACCORDANCE WITH ALL FEDERAL, STATE, PROVINCIAL, AND LOCAL REGULATIONS. IF IN DOUBT, CONTACT PROPER AGENCIES. EPA CHARACTERISTIC: D001

SECTION 14. TRANSPORT INFORMATION

MARINE POLLUTANT: Nο

DOT/TDG SHIP NAME: BULK: NA1993, Combustible liquid, n.o.s. (contains: d-Limonene), PG-III

Combustible liquid. Not DOT regulated on trucks in containers of < 119 gallons.

DRUM LABEL:

None (Combustible Liquid)

IATA / ICAO:

UN1993, Flammable liquids, n.o.s. (contains: d-Limonene), 3, PG-III

IMO / IMDG:

UN1993, Flammable liquids, n.o.s. (contains: d-Limonene), 3, PG-III

EMERGENCY RESPONSE GUIDEBOOK NUMBER: 128

SECTION 15. REGULATORY INFORMATION

EPA REGULATION:

SARA SECTION 311/312 HAZARDS: Fire

All components of this product are on the TSCA list. This material contains no known products restricted under SARA Title II Section 313 in amounts greater or equal to 1%.

STATE REGULATIONS:

THIS PRODUCT MEETS REQUIREMENTS OF SOUTHERN CALIFORNIA AQMD RULE 443.1 & SIMILAR REGULATIONS

CALIFORNIA SAFE DRINKING WATER & TOXIC ENFORCEMENT ACT (PROPOSITION 65): This product contains no chemicals known to the State of California to cause cancer or reproductive toxicity.

INTERNATIONAL REGULATIONS

The identified components of this product are listed on the chemical inventories of the following countries:
Australia (AICS), Canada (DSL or NDSL), China (IECSC), Europe (EINECS, ELINCS), Japan (METI/CSCL, MHLW/ISHL), South Korea (KECI), New Zealand (NZIoC), Philippines (PICCS), Switzerland (SWISS), Taiwan (NECSI), USA (TSCA).

CANADA: WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM (WHMIS)

B3: Combustible Liquid.

D2B: Irritating to skin / eyes.

This product has been classified in accordance with hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all information required by the CPR.

SECTION 16. OTHER INFORMATION

HAZARD RATINGS:

HEALTH (NFPA): 1, HEALTH (HMIS): 1, FLAMMABILITY: 2, PHYSICAL HAZARD: (Personal Protection Rating to be supplied by user based on use conditions.) This information is intended solely for the use of individuals PHYSICAL HAZARD: 0 trained in the NFPA & HMIS hazard rating systems.

See Section 2 for Risk & Safety Statements. Employees should be made aware of all hazards of this material (as stated in this SDS) before handling it.

SDS DATE: 04/20/2014

NOTICE

Bridgepoint Systems disclaims all expressed or implied warranties of merchantability or fitness for a specific use, with respect to the product or the information provided herein, except for conformation to contracted specifications. All information appearing herein is based upon data obtained from manufacturers and/or recognized technical sources. While the information is believed to be accurate, we make no representations as to its

accuracy or sufficiency.
COMPANY IDENTITY: Bridgepoint Systems
PRODUCT IDENTITY: FILTER FREE SDS DATE: 04/20/2014 ORIGINAL: 04/20/2014

SECTION 16. OTHER INFORMATION (CONTINUED)

Conditions of use are beyond our control, and therefore users are responsible for verifying the data under their own operating conditions to determine whether the product is suitable for their particular purposes and they assume all risks of their handling, and disposal of the product. Users also assume all risks in regards to the publication or use of, or reliance upon information contained herein. This information relates only to the product designated herein, and does not relate to its use in combination with any other material or process.

Unless updated, the Safety Data Sheet is valid until 04/20/2017.