



Rust Remover

MSDS Number: B198 Revision Date: November 20, 2013

Page 1 of 6

1

PRODUCT AND COMPANY IDENTIFICATION

Manufacturer

Kärcher North America, Inc. 325 S Price Road Chandler, AZ 85224

 Contact:
 Prochem

 Phone:
 480-899-7000

 Fax:
 480-786-9538

 Email:
 info@prochem.com

 Web:
 www.prochem.com

Product Name: Rust Remover Revision Date: November 20, 2013

Version: 43-72B MSDS Number: B198

Emergency Information: INFOTRAC 1-800-535-5053 International 1-352-323-3500

2

HAZARDS IDENTIFICATION

Route of Entry: Eyes, Skin, Inhalation:

Target Organs: Eyes; Skin; Respiratory system;

Inhalation: Can cause irritation and inflammation of the respiratory tract.Skin Contact: Irritating to skin; may cause burns, blisters and itching.

Eye Contact: Irritating to eyes, eye damage may occur.

Ingestion: Irritating to intestinal tract; may cause burns, vomiting, stomach pain, and disorientation.

NFPA: HMIS III:



Health = 2, Fire = 1, Reactivity = 0 H2/F1/PH0



PERSONAL PROTECTION INDEX								
А	ØØ.			G	₽ Ø+	≠ + 💸	,	
В	Ø Ø + ● €			Н	(T)	- # + 1	+*	
С	Ø Ø + ● + 🕌				<i>⊠</i> Ø+	≠ + ¾		
D	<u>@</u> + = + ★			5	a +	€ + 1	+ 😽	
E	Ø⊠ + = € + @				K	% + - + ↑ + L		
F	F ∞ + + + + + 					Consult your supervisor or S.O.P. for "SPECIAL" handling directions		
A Safety Glasses	N	n Goggles	O Face Shield & Eye Protection	p Glove	*	q [Synthetic Apron	S T
t Dust Respirat	© or	U Wapor Respirator	W Dust & Vapor Respirator	y Full Fa Respire		Airline Hood or Mask	Additional Info	mation





Rust Remover

MSDS Number: B198 Revision Date: November 20, 2013

Page 2 of 6

GHS Hazard Pictograms:





GHS Classifications:

Health, Acute toxicity, 4 Oral Health, Acute toxicity, 4 Dermal Health, Serious Eye Damage/Eye Irritation, 1

GHS Phrases:

Warning, H302 - Harmful if swallowed

Warning, H312 - Harmful in contact with skin

Danger, H318 - Causes serious eye damage

GHS Precautionary Statements:

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Wear protective gloves/protective clothing/eye protection/face protection.

IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.

IF ON SKIN: Wash with soap and water.

IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do.

Continue rinsing.

Wash contaminated clothing before reuse.

3 HAZARDS IDENTIFICATION

Ingredients:

CAS # Percentage	Chemical Name
144-62-7 <9%	Oxalic acid (as dihydrate)
112-34-5 <5%	Diethylene glycol monobutyl ether
7664-38-2 <6%	Phosphoric acid

OSHA Regulatory Status:

This SDS contains valuable information critical to the safe handling and proper use of this product. This SDS should be retained and available for employees and other users of this product.





Rust Remover

MSDS Number: B198 Revision Date: November 20, 2013

Page 3 of 6

4 FIRST AID MEASURES

Inhalation: Remove from exposure and get fresh air. Keep warm and at rest. Get medical attention immediately if artificial

respiration is required.

Skin Contact: Remove contaminated clothing, jewelry and shoes immediately. Flush affected area with large amounts of water, then

use soap or mild detergent and large amounts of water for 15-20 minutes to cleanse area. If skin is severely irritated or

burned, get medical attention immediately.

Eye Contact: Immediately flush eyes with large amounts of water occasionally lifting upper and lower lids for at least 15 minutes. Get

immediate medical attention.

Ingestion: Rinse mouth with water. DO NOT INDUCE VOMITING unless instructed to by medical personnel. If vomiting occurs

keep head lower than hips to help prevent aspiration. If person is unconscious, do not induce vomiting; turn their head

to the side. Never make an unconscious person vomit or drink fluids. Get medical attention.

5 FIRE FIGHTING MEASURES

Flash Point: 100 ° C / 212 ° F Flash Point Method: Closed Cup

Wear self-contained breathing apparatus and other protective clothing. Use any standard agent - choose the one most appropriate for type of surrounding fire.

6 ACCIDENTAL RELEASE MEASURES

Isolate area; keep unnecessary personnel away. Do not discharge into drains. Ventilate closed spaces before entering. Prevent further leakage or spillage if safe to do so. Prevent entry into waterways, sewers, basements or confined areas. Wear appropriate protective equipment and clothing during cleanup. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal.

7 HANDLING AND STORAGE

Handling Precautions: Do not get in eyes, on skin, or on clothing. Do not breathe vapor. Keep container closed. Promptly clean

up spills. Wash thoroughly after handling.

Storage Requirements: Store out of reach of children; keep container closed; store in a cool, well-ventilated place.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls: Normal room ventilation is satisfactory for limited use.

Personal Protective Equip: HMIS PP, B | Safety glasses, Gloves

Phosphoric Acid 7664-38-2 OSHA PEL 1 mg/m3

9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Opaque off-white

Physical State:LiquidOdor:SassafrasSpec Grav./Density:8.82 lb/galSolubility:Soluble

pH: 0.5 - 1.5





Rust Remover

MSDS Number: B198 Revision Date: November 20, 2013

Page 4 of 6

10

STABILITY AND REACTIVITY

Stability: Product is stable under normal conditions.

Conditions to Avoid: None Known

Materials to Avoid: Strong oxidizing or acidic materials

Hazardous Decomposition: Exposure to fire may liberate carbon dioxide, carbon monoxide, organic acids, and other unidentified

thermal decomposition products from this product or its packaging.

Hazardous Polymerization: Will not occur.

11

TOXICOLOGICAL INFORMATION

Toxicity Data:

Oxalic Acid 144-62-7

Oral (LD 50): Not listed on RTECS

Intraperitoneal (injection) 270 mg/kg - Mouse

Inhalation (LC 50): Not listed on RTECS

Skin irritation: Mild

Eye irritation: Severe

Sensitation: Not considered an occupational sensitizer

Diethylene glycol butyl ether 112-34-5

Oral (LD 50): 5660 mg/kg - Rat

Inhalation (LC 50): Not listed on RTECS

Skin irritation: Moderate

Eye irritation: Severe

Sensitation: Not considered an occupational sensitizer

Phosphoric Acid 7664-38-2

Oral (LD 50): 1200 mg/kg - Rat

Inhalation (LC 50): 25.5 mg/m3 - rat

Skin irritation: Severe

Eye irritation: Severe

Sensitation: Not considered an occupational sensitizer





Rust Remover

MSDS Number: B198 Revision Date: November 20, 2013

Page 5 of 6

12

ECOLOGICAL INFORMATION

On the basis of available information, this material is not expected to produce any significant environmental effects when recommended use instructions are followed.

13

DISPOSAL CONSIDERATIONS

Dispose of in accordance with all applicable regulations.

14

TRANSPORT INFORMATION

Gallon case - Limited Quantity 5/55 gallon - UN1760 Corrosive liquids, n.o.s., (Oxalic acid), 8, III Ship in accordance with 49 CFR parts 100-185.

15

REGULATORY INFORMATION

COMPONENT / (CAS/PERCENT) / CODES

*Oxalic acid (as dihydrate) (144627 <9%) MASS, OSHAWAC, PA, TSCA, TXAIR, WHMIS

*Diethylene glycol monobutyl ether (112345 <5%) TSCA, WHMIS

*Phosphoric acid (7664382 <6%) CERCLA, CSWHS, EPCRAWPC, MASS, NJHS, OSHAWAC, SARA313, TSCA, TXAIR, WHMIS

REGULATORY KEY DESCRIPTIONS

All components are listed on TSCA

CERCLA = Superfund clean up substance
CSWHS = Clean Water Act Hazardous substances
EPCRAWPC = EPCRA Water Priority Chemicals
MASS = MA Massachusetts Hazardous Substances List
NJHS = NJ Right-to-Know Hazardous Substances
OSHAWAC = OSHA Workplace Air Contaminants
PA = PA Right-To-Know List of Hazardous Substances
SARA313 = SARA 313 Title III Toxic Chemicals
TXAIR = TX Air Contaminants with Health Effects Screening Level
WHMIS = Workplace Haz Mat Info Sys Canada





Rust Remover

MSDS Number: B198 Revision Date: November 20, 2013

Page 6 of 6

16

OTHER INFORMATION

This document is prepared in accordance with 29 CFR 1910.1200. The purpose of this section is to ensure that the hazards of all chemicals produced or imported are evaluated, and that information concerning their hazards is transmitted to employers and employees.

All information appearing herein is based upon data obtained from the raw material manufacturer and/or recognized technical sources. While the information above is believed to be true and accurate, the author makes no representations as to its accuracy or sufficiency. Conditions of use are beyond the manufacturer's control; therefore the users are responsible to verify this data under their own particular conditions, applications and regulations to determine if the product is suitable for their particular purposes. The users assume all risks of product use, handling, disposal, reliance upon, publication or use of the information contained herein. This information applies only to the product designated above and does not necessarily apply to its use in combination with other materials, products, chemical compounds, structures or processes.

Prepared by: EHS Manager Phone: 480-899-7000