



Ultrapac Trafficlean VOC

MSDS Number: S712

Revision Date: November 12, 2013

Page 1 of 5

1

PRODUCT AND COMPANY IDENTIFICATION

Manufacturer

Kärcher North America, Inc. Prochem 325 S. Price Road Chandler, AZ 85224

Phone:	480-899-7000
Fax:	480-786-9538
Email:	info@prochem.com
Web:	www.prochem.com

Product Name:Ultrapac Trafficlean VOCRevision Date:November 12, 2013Version:44-43IMSDS Number:S712

Emergency Information: INFOTRAC 1-800-535-5053 International 1-352-323-3500

2	HAZARDS IDENTIFICATION		
Route of Entry:	Eyes; Skin; Inhalation;		
Target Organs:	Eyes; Skin;		
Inhalation:	Minimal respiratory tract irritation may occur with exposure to a large amount of material.		
Skin Contact:	May cause irritation.		
Eye Contact:	May cause irritation.		
Ingestion:	Ingestion is not applicable route of entry for intended use.		
NFPA: HMIS III:	Health = 1, Fire = 2, Reactivity = 0 H1/F2/PH0	PERSONAL PROTECTION INDEX	
		A Ø2 G Ø2+€+₩	
NFPA FIRE HAZARI		B 🕫 + 🗲 H 🛱 + 🕷	
	HEALTH 🖌 1	C ፼ + ≠ + ∔ ፼ + ≠ + ¥	



 HMIS III

 HEALTH
 ☑
 I

 FLAMMABILITY
 ☑
 I

 PHYSICAL HAZARDS
 0
 I

 PERSONAL PROTECTION B | Safety Glasses, gloves
 I
 I

D 647 + 📫 + 1 J 3 Ε Κ -**V**V + + 🗲 + 🏌 + 🗲 + Consult your supervise or S.O.P. for "SPECIAL" F + 😽 N AV a 0 A q 飠 u w t 50 . 9 Ŷ 1

GHS Classifications:

Physical, Flammable Liquids, 4 Health, Acute toxicity, 5 Dermal

GHS Phrases:

SDS Safety Data Sheet Prochem



Ultrapac Trafficlean VOC

MSDS Number: S712

Revision Date: November 12, 2013 Page 2 of 5

Warning, H227 - Combustible liquid Warning, H313 - May be harmful in contact with skin

GHS Precautionary Statements:

Keep away from heat/sparks/open flames/hot surfaces. No smoking Wear protective gloves/protective clothing/eye protection/face protection. In case of fire: Use ABC fire extinguisher for extinction. Store in a well ventilated place. Keep cool. Call a POISON CENTER or doctor/physician if you feel unwell.

GHS Hazard Pictograms: No GHS Pictograms

3

COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients:

Cas #	Percentage	Chemical Name
111-76-2	<3%	Ethylene Glycol Butyl Ether
112-34-5	<8%	Diethylene Glycol Butyl Ether

OSHA Regulatory Status:

This SDS contains valuable information critical to the safe handling and proper use of this product. This SDS should be retained and available for employees and other users of this product.

4	FIRST AID MEASURES
Inhalation:	If symptoms develop, move victim to fresh air; if symptoms persist, obtain medical attention.
Skin Contact:	Wash with soap and water. If irritation persists consult medical personnel.
Eye Contact:	Immediately flush eyes with large amounts of water for at least 15 minutes, lifting eyelids occasionally to facilitate irrigation. Get immediate medical attention.
Ingestion:	If swallowed, DO NOT induce vomiting unless directed to do so by medical personnel. If injured party is conscious, give two glasses of water. Seek medical attention.
ingestion:	

5	FIRE FIGHTING MEASURES	
Flash Point	183º F	

Closed Cup

Flash Point Method:

Wear self-contained breathing apparatus and other protective clothing. Use any standard agent - choose the one most appropriate for type of surrounding fire.

6

ACCIDENTAL RELEASE MEASURES

Keep away from drains and ground water. Keep all unnecessary personnel away. Spill area may be slippery. Pick up excess with inert absorbent material and place into separate waste container. Ventilate area and wash spill site after material pickup is complete. Consult an expert on disposal of recovered material and ensure conformity to local disposal regulations.





Ultrapac Trafficlean VOC

MSDS Number: S712

Revision Date: November 12, 2013

Page 3 of 5

HANDLING AND STORAGE

Handling Precautions:Avoid contact with eyes, skin, or clothing; Consider normal working hygiene. Handle with care and avoid
spillage on the floor (slippage). Keep away from sources of ignition; wash thoroughly after handling.Storage Requirements:Keep away from children. Store in cool/dry area; Keep container closed.

8

9

7

EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls:Normal room ventilation is satisfactory for limited use.Personal Protective Equip:HMIS PP, B | Safety glasses, Gloves

Ethylene glycol butyl ether 111-76-2 OSHA PEL 50 ppm - 240 mg/m3

PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Physical State: Spec Grav./Density: pH: Opaque carmel Liquid 9.48 lb/gal 9.5 as is

Odor: Solubility: Mint Soluble

10 STABILITY AND REACTIVITY Stability: Product is stable under normal conditions. Conditions to Avoid: None known

Conditions to Avoid: Materials to Avoid: Hazardous Decomposition: Product is stable under normal conditions. None known None known Exposure to fire may liberate carbon dioxide, carbon monoxide, organic acids, and other unidentified thermal decomposition products from this product or its packaging. Will not occur.

Hazardous Polymerization:

TOXICOLOGICAL INFORMATION

Toxicity Data:

11

Ethylene glycol butyl ether 111-76-2

Oral (LD 50): 917 mg/kg - Rat

Inhalation (LC 50): 2900 mg/m3/7H - Rat

Skin irritation: Mild

Eye irritation: Mild

Sensitation: Not considered an occupational sensitizer

Diethylene glycol butyl ether 112-34-5

Oral (LD 50): 5660 mg/kg - Rat

Inhalation (LC 50): Not listed on RTECS

Skin irritation: Moderate





Ultrapac Trafficlean VOC

MSDS Number: S712

Revision Date: November 12, 2013

Page 4 of 5

Eye irritation: Severe

Sensitation: Not considered an occupational sensitizer

12 ECOLOGICAL INFORMATION

On the basis of available information, this material is not expected to produce any significant environmental effects when recommended use instructions are followed.

13

DISPOSAL CONSIDERATIONS

Dispose of in accordance with local regulations.

14 TRANSPORT INFORMATION

Ship in accordance with 49 CFR parts 100-185. Non-hazardous for air, sea and road freight.

15	REGULATORY INFORMATION
COMPONENT / (CAS/PERC) / CODES	
*Ethylene Glycol Butyl Ether (111762 <3%) MASS, OSHAWAC, PA, TSCA, TXAIR, WHMIS	
*Diethylene Glycol Butyl Ether (112345 <8%) SARA313, TSCA, WHMIS	
REGULATORY KEY DESCRIPTIONS	
All components are listed on TSCA	
MASS = MA Massachusetts Hazardous Substances List OSHAWAC = OSHA Workplace Air Contaminants PA = PA Right-To-Know List of Hazardous Substances SARA313 = SARA 313 Title III Toxic Chemicals TXAIR = TX Air Contaminants with Health Effects Screening Level WHMIS = Workplace Haz Mat Info Sys Canada	

16 OTHER INFORMATION

This document is prepared in accordance with 29 CFR 1910.1200. The purpose of this section is to ensure that the hazards of all chemicals produced or imported are evaluated, and that information concerning their hazards is transmitted to employers and employees.

All information appearing herein is based upon data obtained from the raw material manufacturer and/or recognized technical sources. While the information above is believed to be true and accurate, the author makes no representations as to its accuracy or sufficiency. Conditions of use are beyond the manufacturer's control; therefore the users are responsible to verify this data under their own particular conditions, applications and regulations to determine if the product is suitable for their particular purposes. The users assume all risks of product use, handling, disposal, reliance upon, publication or use of the information contained herein. This information applies only to the product designated above and does not necessarily apply to its use in combination with other materials, products, chemical compounds, structures or processes.





MSDS Number: S712

Ultrapac Trafficlean VOC

Revision Date: November 12, 2013Page5of5