

HydraFRESH LVC



HARD SURFACE

RTU pH 6.5 - 7.5

Laminate, Wood, and
Luxury Vinyl
Plank and Tile
Floors

Restorative Cleaner for Tile, Laminate, and Luxury Vinyl Plank Floors

Restoring the appearance of your luxury vinyl plank or luxury vinyl tile flooring investment to "like-new" condition is more than just cleaning.

HydraFRESH LVC takes a comprehensive approach that can penetrate deep into the grooves and textured surfaces of your floor for a higher level of soil removal that eliminates dirt, scuffs, grease, and other potentially harmful contaminants.



- Contains special soil inhibitors and is a low residue formula that does not contain any sticky or tacky cleaning agents.
- Can be used as part of a prespray and rinse system or as part of a no rinse system.
- Neutral PH makes it safe for luxury vinyl plank and tile floors, resilient tile floors and wood (polyurethane finish only) and laminate floors.
- HydraFRESH LVC allows you to extend the life of the flooring investment and keep it looking great all the time.

Directions:

Please read the full label directions before cleaning.

1. Sweep or vacuum floors prior to deep cleaning to remove particulate soils. An untreated microfiber dust mop works well for this. HydraFRESH LVC can be used in conjunction with a counter rotating brush agitation system with the appropriate brushes, an auto-scrubber; a mop and rinse system, and where the construction of the floor and the adhesives allow, a rotary hard surface cleaning tool such as the RX15H Rotary Hard Surface Tool, the RX20 NEXT GEN with hard surface attachments; or a stationary hard surface wand.
2. For normal soiling, Mix 1 part HydraFRESH LVC with 64 parts water into sprayer (2 ounces of solution/gallon of water). For heavy soiling, mix 1 part HYDRAFRESH LVC with 16 parts water (16 ounces of solution/gallon of water).
3. Apply with sprayer or mop
4. Allow several minutes of dwell time but do not allow solution to dry.
5. Ground in soiling in grooves and textured surfaces may require agitation with a counter rotating brush system with appropriate brushes
6. Agitate and extract cleaning solution using high pressure warm or hot water from RX15H Rotary Hard Surface Tool or a RX20 NEXTGEN with a hard surface attachment, or high pressure hard surface wand. For more sensitive surfaces, consider using a hard surface wand or simply mop with clean water and rinse. Consult with the flooring manufacturer directions for further information on what rinse or extraction system to use.
7. For faster drying, especially in humid environments, consider the use of an axial, centrifugal, or downdraft air mover after cleaning.

Available in: 1 Gallon, Case of 4 x 1 Gallon,
1 Quart, 4 x 1 Quart Case

Part # 800-142

HydraMaster
We've Got Your Back



www.hydramaster.com | 800.426.1301 | 425.775.7272
sales@hydramaster.com